

	<p align="center"><b>STANDARD OPERATING POLICY AND PROCEDURE</b></p> <p align="center">Community and Economic Development</p>	<p>Number:</p> <p align="center"><b>6-1</b></p>
<p><b>Subject:</b>     <b>Grease and Gray Water Drainage Pipe Identification</b></p>		<p><b>Approval Date:</b> February 2, 2005</p>
<p><b>Approval:</b>    Chuck King, Building Official</p>		<p><b>Effective Date:</b> February 2, 2005</p>

## 1.0 PURPOSE

In order to reduce the potential for health hazards, identification for grease and gray water drainage pipes is required.

## 2.0 DISTRIBUTION

Public, Community and Economic Development (CED) Personnel

## 3.0 REVISION HISTORY

Updated February, 2016  
January, 2019 (code update)

## 4.0 CODE REFERENCE

2018 International Plumbing Code (IPC), Section 1004 and 1302.4

## 5.0 POLICY

A means of identification or method for marking all grease and / or gray water drainage pipes shall be included with the construction documents submitted for a permit, and utilized during construction of these systems. Examples of a means of identification are as follows:

1. A **continuously stenciled identification** along the grease or gray water drain pipe. Stenciling shall not deteriorate under the conditions of use, or have an adverse effect on the pipe material.
2. **Continuous tape** identifying the use of the pipe as grease or gray water drain piping may be placed directly above the pipe, or wrapped around the pipe in a manner that identifies the use of the pipe. When utilizing wrapped pipe identification, the identification shall be clear at intervals not to exceed twelve inches.

Other methods proposed shall provide clear identification for the intended use of the pipe. All other methods shall be approved by the *building official* prior to installation and use.